

NLS 325 series roof light (Galvanised Steel)

Supplier	NaturaLight Systems Ltd.
Type	NLS 325 (Slimline hit & miss ventilation with cowl and double skin rooflight).
Material	Galvanised steel to EN 10142.
Finish	Polyester powder coated to BS 6496.
Insulation	13mm Retrofit fibre board to EN 13169.
Kerb dimensions	225 high to underside of vent.
Ventilation	86cm ² .
Fixings	Stainless steel security fixings.
Roof light	3mm x 3mm UV protected high impact polycarbonate.
Certification	British Board of Agrément [BBA] (technical approval for construction).
Classification	Non-fragile [BRE]. (Building Research Establishment Classification).
Glazing Spec	Dome/Pyramid.
Fire rating	BS 476 pt 3 AA rating. BS 476 pt 7 Class 1 (materials which achieve class 1 (or 1y) can be classed as an AA designation. 1991 Building regulations Tp(a) on 3mm or over.

Supplier	NaturaLight Systems Ltd.
Type	NLS 325 (Slimline hit & miss ventilation with cowl and double skin rooflight with burglar bars).
Material	Galvanised steel to EN 10142.
Finish	Polyester powder coated to BS 6496.
Insulation	13mm Retrofit fibre board to EN 13169
Kerb dimensions	225 high to underside of vent.
Ventilation	86cm ² .
Fixings	Stainless steel security fixings.
Roof light	3mm x 3mm UV protected high impact polycarbonate.
Certification	British Board of Agrément [BBA] (technical approval for construction).
Classification	Non-fragile [BRE]. (Building Research Establishment Classification).
Security	Burglar Bars 12mm x 12mm solid high tensile steel bars
Glazing Spec	Dome/Pyramid.
Fire rating	BS 476 pt 3 AA rating. BS 476 pt 7 Class 1 (materials which achieve class 1 (or 1y) can be classed as an AA designation. 1991 Building regulations Tp(a) on 3mm or over.

Supplier	NaturaLight Systems Ltd.
Type	NLS 325 (Slimline hit & miss ventilation with cowl) and Triple skin rooflight.
Material	Galvanised steel to EN 10142.
Finish	Polyester powder coated to BS 6496.
Insulation	13mm Retrofit fibre board to EN 13169.
Kerb dimensions	225 high to underside of vent.
Ventilation	86cm ² .
Fixings	Stainless steel security fixings.
Roof light	3mm x 3mm x 3mm UV protected high impact polycarbonate.
Certification	British Board of Agrément [BBA] (technical approval for construction).
Classification	Non-fragile [BRE]. (Building Research Establishment Classification).
Glazing Spec	Dome/Pyramid.
Fire rating	BS 476 pt 3 AA rating. BS 476 pt 7 Class 1 (materials which achieve class 1 (or 1y) can be classed as an AA designation. 1991 Building regulations Tp(a) on 3mm or over.

Supplier	NaturaLight Systems Ltd.
Type	NLS 325 (Slimline hit & miss ventilation with cowl) and triple skin rooflight with burglar bars.
Material	Galvanised steel to EN 10142.
Finish	Polyester powder coated to BS 6496.
Insulation	13mm Retrofit fibre board to EN 13169.
Kerb dimensions	225 high to underside of vent.
Ventilation	86cm ² .
Fixings	Stainless steel security fixings.
Roof light	3mm x 3mm x 3mm UV protected high impact polycarbonate.
Certification	British Board of Agrément [BBA] (technical approval for construction).
Classification	Non-fragile [BRE]. (Building Research Establishment Classification).
Security	Burglar Bars 12mm x 12mm solid high tensile steel bars
Glazing Spec	Dome/Pyramid.
Fire rating	BS 476 pt 3 AA rating. BS 476 pt 7 Class 1 (materials which achieve class 1 (or 1y) can be classed as an AA designation. 1991 Building regulations Tp(a) on 3mm or over.