



Specification for NaturaLight Systems Limited
NLS L2 Securiglaze Kerb & NLS200/220 Rooflight
with Hit & Miss Ventilation.

<u>Manufacturer:</u>	NaturaLight Systems Limited Accessory House Barrington Industrial Estate Bedlington Northumberland NE22 7DQ E mail: info@naturalight.co.uk Tel: 01670 530333 Fax: 01670 824540
<u>Client:</u>	TBC
<u>Project Ref:</u>	TBC
<u>NLS Contact Name:</u>	TBC
<u>Product Reference:</u>	NLS L2 Securiglaze 112mm high kerb – Hit & Miss Ventilation
<u>Glazing:</u>	System to be used with a range of high performance glass ranging from 24.4mm-30.8mm.
<u>Kerb Material:</u>	Extruded from high grade Upvc, self-insulating upstand 112mm high with suitable fixing flange to allow direct fixing to roof raised upstand or direct mounting to any of the NLS kerb range.
<u>Ventilation</u>	Titon Hit & Miss Vents to 2 or 4 sides for manual ventilation 2 sides = 5550mm ² Airflow – Based on 1200x1200 Size 4 Sides = 11100mm ² Airflow – Based on 1200x1200mm Size
<u>Fixing:</u>	Security Fixings stainless steel grade A2 to British Standard 6105 (grade 304).
<u>Base Fixing Type:</u>	Suitable for fixing onto prepared roof raised upstand. Secured through internal of rooflight frame for concealed fixing.
<u>Non-fragility:</u>	Tested by the BRE for non-fragility and achieving class ‘B’ rating.

