



Specification for NaturaLight Systems Limited
NLS L2 Securiglaze Kerb & NLS200/220 Rooflight
With Manually Operated Opening

<u>Manufacturer:</u>	NaturaLight Systems Limited Accessory House Barrington Industrial Estate Bedlington Northumberland NE22 7DQ E mail: info@naturalight.co.uk Tel: 01670 530333 Fax: 01670 824540
<u>Client:</u>	TBC
<u>Project Ref:</u>	TBC
<u>NLS Contact Name:</u>	TBC
<u>Product Reference:</u>	NLS L2 Securiglaze 112mm high kerb- Manual wormgear
<u>Glazing:</u>	System to be used with a range of high performance glass ranging from 24.4mm-30.8mm.
<u>Kerb Material:</u>	Extruded from high grade Upvc, self-insulating upstand 112mm high with suitable fixing flange to allow direct fixing to roof raised upstand or direct mounting to any of the NLS kerb range.
<u>Ventilation</u>	Manual Hinged ventilation consisting of wormgear screw mechanism, operated by pole.
<u>Fixing:</u>	Security Fixings stainless steel grade A2 to British Standard 6105 (grade 304).
<u>Base Fixing Type:</u>	Suitable for fixing onto prepared roof raised upstand or NLS kerb range. Secured through internal of rooflight frame for concealed fixing
<u>Non-fragility:</u>	Tested by the BRE for non-fragility and achieving class 'B' rating.

